The Florida Advanced Technological Education (FLATE) Center wishes to make available, for educational and noncommercial purposes only, materials relevant to the "EST1830 Introduction to Alternative/Renewable Energy" course comprised of images, texts, facilitator's notes, and other demonstration materials.

This instructional resource forms part of FLATE's outreach efforts to facilitate a connection between students and teachers throughout the State of Florida. We trust that these activities and materials will add value to your teaching and/or presentations.

FLATE Hillsborough Community College - Brandon 10414 E Columbus Dr., Tampa, FL 33619 (813) 259-6575 www.fl-ate.org; www.madeinflorida.org; www.fesc.org

This material is based upon work supported by the National Science Foundation under Grant No. 0802434 and a Florida Energy Systems Consortium Grant. Any opinions, findings, and conclusions or recommendations expressed in this material are those of the author(s) and do not necessarily reflect the views of the National Science Foundation or the Florida Energy Systems Consortium.

Introduction to Alternative and Renewable Energy

EST1830






3. Energy Production

3.1 Renewable Energy Technologies3.1.1 Solar Energy


3. Energy Production

- 3.1.1 Solar Energy
 - 3.1.1a Sun's Position
 - 3.1.1b Sun Path
 - 3.1.1c Irradiation
 - 3.1.1d Air Mass
 - 3.1.1e Irradiance on Plate
- 3.1.1.1 Photovoltaics
- 3.1.1.2 Solar Thermal
 - 3.1.1.2a Low Temperature Collectors
 - 3.1.1.2b Medium Temperature Collectors
 - 3.1.1.2c High Temperature Collectors



(insolation), then 70% of power is $P=1.25\times10^{17}$ W at the upper atmosphere.

3.1.1 Solar Irradiance



On the daylight side, only the point directly under the Sun receives fullintensity solar radiation. From the equator to the poles, the Sun' rays meet Earth at smaller and smaller angles, and the light gets spread over larger and larger surface areas (red lines). (NASA illustration by Robert Simmon.)

(1) The total solar irradiance (P) is the maximum possible power that the Sun can deliver to Earth's average distance from the Sun. But as the earth rotates this power is distributed across the entire surface area $(4\cdot\pi\cdot R_{E}^{2})$. Only half the Earth is ever lit by the Sun at one time, which **halves** the total solar irradiance.


(2) Total solar irradiance is the maximum power the Sun can deliver to a surface that is perpendicular to the path of incoming light. Because the Earth is approximated as a sphere, only areas near the equator at midday come close to being perpendicular to the path of incoming light. Everywhere else, the light comes in at an angle. The progressive decrease in the angle of solar illumination with increasing latitude reduces the average solar irradiance by an **additional one-half.**

So, P=3.13 ×10¹⁶ W shining on the earth

3.1.1 Solar Irradiance


- P=3.13 ×10¹⁶ W is equal to 31300 TW of average solar power hitting the earth's surface over a year.
 - This is about 2.74 ×10¹⁷ kW-h per year
- Remember
 - US consumes ~ 3.5 TW of energy per year
 - World ~ 15 TW each year
 - But, energy consumption is more than just electricity

3.1.1 Solar Irradiance Cycle



Sun has an 11-year cycle driven by dark sunspots and bright faculae.

Current Solar Constant: 1366 W/m²




•From Earth's perspective, sun appears to revolve around the earth. Ancient geocentric view. •Ecliptic

• The apparent path of the Sun's motion on the celestial sphere as seen from Earth is called the ecliptic.


•The ecliptic plane is tilted 23.5° with respect to the plane of the celestial equator since the Earth's spin axis is tilted 23.5° with

January 27, 2011 respect to its orbit around the sun Late-Fesc


Farth's Orbit around sun



3.1.1a Seasonal Declination Change




2




FLATE-FESC

January 27, 2011

3.1.1a Earth's Orbit



3.1.1a Earth's Orbit



3.1.1a Vernal Equinox at Chichen Itza



Location: 20º 40' 01 N (20.6667) 88º 34'09 W (-88.6)

January 27, 2011

http://www.world-mysteries.com/chichen kukulcan.htm

•Vernal Equinox: March 21

- •Between 3:30-5:50pm local time
- •Built around 800AD
- •Structure oriented about 17 degrees

FLATE-Feast of true north to get the effect.

3.1.1a Vernal Equinox at Chichen Itza






Location: 20º 40' 01 N (20.6667) 88º 34'09 W (-88.6)

January 27, 2011

http://www.satimagingcorp.com/galleryimages/IKSChichen Itza Mexico 05-MAR-2001 copyrighted.jpg


3.1.1a Vernal Equinox at Chichen Itza



Earth position relative to the sun at Vernal Equinox: March 21

http://www.montgomerycollege.edu/Departments/planet/M_AS102/coordinates/LatitudeLongitudeEarth.html

3.1.1a Elliptical Orbit



3.1.1a Solar Irradiance


- Solar Irradiance (Incident Solar Radiation → Insolation)
- Solar Constant: 1366 W/m²
 - Measured in terms of Power per unit area
 - "Constant" is really a yearly average.
 - Because, earth's orbit around sun is elliptical
 - Aphelion (point in orbit when earth is the farthest away from sun): 152x10⁶ km around July 4.
 - Perihelion (point in orbit when earth is closest to the sun): 147x10⁶ km around January 3.
 - So earth is closest to sun during Florida winter, but farthest away from sun during the summer.
 - Does not take into account sun's 11-year cycle.
- The intensity of solar radiation falling on earth changes according to season


3.1.1a Orbit Ellipticity of Planets

Solar Irradiance at the Planets										
Planet	Solar Irradiance, W*m ⁻²									
	Mean	Perihelion	Aphelion							
Mercury	9116.4	14447.5	6271.1							
Venus	2611.0	2646.4	2575.7							
Earth	1366.1	1412.5	1321.7							
Mars	588.6	715.9	491.7							
Jupiter	50.5	55.7	45.9							
Saturn	15.04	16.76	13.53							
Uranus	3.72	4.11	3.37							
Neptune	1.510	1.515	1.507							
134340Pluto*	0.878	1.571	0.560							

3.1.1a Solar Irradiance


Solar Irradiance can be estimated for each day of the year using this empirical relation. n=day of the year: Jan 1=1; Jan 2=2....Dec 31=365....and I_{sc} is the solar constant.





3.1.1a Irradiation


- BUT...we are not as interested in the overall solar irradiance when putting up a fixed plate solar panel....we are more interested in irradiation on a fixed plate. (more about this later)
- A general analysis concludes that the energy available from sunlight on any fixed plate solar panel on earth depends on
 Time of year: Summer, Fall, Winter, Spring
 Location: Latitude/Longitude
 Time of Day



http://www.montgomerycollege.edu/Departments/planet/M AS102/coordinates/LatitudeLongitudeEarth.html

3.1.1b Sun Path


Sun Path during winter solstice, equinox, and summer solstice



(1) From the earth's perspective we will see the sun tracing a path from east to west according to the time of day.

(2) We will also see a variation in the sun's angular position relative to the earth's horizon depending on time of vear.


- A geocentric viewpoint helps us to locate our fixed solar panels and tilt them to the best angle possible so that the sun's rays hit them at a perpendicular angle (90°).
- For fixed panels, the maximum energy output can be achieved when • their surfaces are perpendicular to the sun at solar noon.
- Solar noon is the point in time when the sun is at its daily zenith (may or ^{Jan}mäynnot be 12 o'clock). FLATE-FESC http://www.redrok.com/images/sunpath.gif




To use this chart for southern latitudes, reverse horizontal axis (east/west & AM/PM)

23

3.1.1b Sun Path






3.1.1b Sun Path

 For fixed panels, the maximum energy output can be achieved when their surfaces are perpendicular to the sun at solar noon.


- The panels must be tilted to the best angle possible.
- But, that depends on the time of year and location on earth.
- NREL suggests that they be tilted at an angle equal to the site's latitude.

NREL: To optimize performance


- Winter: collector should be tilted 15° > than latitude
- Summer: collector should be tilted 15° < than latitude



3.1.1b Fixed Solar Panel Angles



Find the latitude of your site on the y-axis (right hand side), then follow the line that corresponds most closely to your site and using the numbered days on the xaxis read the panel angle off the y-axis on the left hand side.




January 27, 2011


3.1.1c Irradiation

- Irradiation is not the same as Irradiance...sorry about the names.
 - Irradiation is measured in units of energy per unit area (J/m²) or (kWh/m²) as opposed to Irradiance which is measured in power per unit area (W/m²).
 - Think of solar irradiance as the power given off by the sun and irradiation as the energy (or radiation) from the sun to which a solar panel is exposed over a period of time (one day for example).
 - Irradiation is usually represented by the symbol H, whereas irradiance is represented by E

3.1.1c Irradiation



3.1.1c Irradiation Data





LATITUDE: 27.97° N LONGITUDE: 82.53° W ELEVATION: 3 meters MEAN PRESSURE: 1018 millibars

STATION TYPE: Secondary

http://rredc.nrel.gov/solar/pubs/redbook/PDFs/FL.PDF

Solar Radiation for Flat-Plate Collectors Facing South at a Fixed Tilt (kWh/m²/day), Uncertainty ±9%

Tilt (°)		Jan	Feb	Mar	Apr	May	June	July	Aug	Sept	Oct	Nov	Dec	Year
0	Average	3.2	4.0	5.1	6.2	6.4	6.1	5.8	5.5	4.9	4.4	3.6	3.1	4.9
	Min/Max	2.6/3.7	3.4/4.5	4.3/5.6	5.8/6.8	5.7/7.1	5.1/6.9	5.1/6.4	4.6/6.3	4.3/5.4	3.6/4.9	3.0/4.0	2.7/3.5	4.5/5.2
Latitude -15	Average	3.9	4.6	5.5	6.4	6.4	5.9	5.7	5.5	5.2	5.0	4.2	3.8	5.2
	Min/Max	3.0/4.6	3.8/5.3	4.7/6.1	5.9/7.1	5.7/7.0	5.0/6.7	5.0/6.3	4.7/6.3	4.5/5.8	4.0/5.6	3.4/4.8	3.1/4.4	4.7/5.5
Latitude	Average	4.5	5.1	5.8	6.3	6.0	5.5	5.3	5.4	5.2	5.4	4.8	4.4	5.3
	Min/Max	3.3/5.3	4.2/5.9	4.8/6.4	5.9/7.0	5.4/6.6	4.7/6.2	4.7/5.9	4.5/6.2	4.5/5.9	4.1/6.1	3.8/5.6	3.5/5.2	4.8/5.7
Latitude +15	Average	4.8	5.3	5.7	5.9	5.3	4.8	4.7	4.9	5.0	5.5	5.1	4.7	5.1
	Min/Max	3.5/5.8	4.3/6.2	4.7/6.4	5.4/6.5	4.8/5.8	4.1/5.3	4.2/5.2	4.2/5.6	4.3/5.7	4.1/6.2	4.0/6.0	3.7/5.7	4.6/5.5
90 January 27, 2	Average	4.0	4.0	3.5	2.8	2.0	1.7	1.8	2.2	2.9	3.9	4.2	4.1	3.1
	Min/Max	2.8/5.0	3.2/4.8	3.0/4.0	2.6/3.0	1.9/2.1	E-FESC6/1.8	1.7/1.9	2.0/2.4	2.4/3.2	2.8/4.4	3.1/5.0	3.1/5.0	2.7/3.3

3.1.1c Irradiation

- A general analysis concludes that the energy available from sunlight on any fixed plate solar panel on earth depends on
 - ☑ Time of year: Summer, Fall, Winter, Spring
 - ✓ Location: Latitude/Longitude
 - ☑ Time of Day

But it also depends on,


Atmospheric Absorption

3.1.1.d Air Mass

Not all of the sun's rays reach earth....recall our discussion on atmospheric absorption.

How much energy does light lose in traveling from the edge of the atmosphere to the surface of the Earth?

Air mass (AM) is the term used to describe the relative path length that the sun's rays have to traverse through the atmosphere before reaching the ground. An AM=1 condition occurs when the sun is directly overhead at a sea-level site; air mass values of 10 or greater occur near sunrise and sunset.



This energy loss depends on the thickness of the atmosphere that the sun's energy must pass through. The radiation that reaches sea level at high noon in a clear sky is 1000 W/m² and is described as "air mass 1" (or AM1) radiation. As the sun moves lower in the sky, the light passes through a greater thickness (or longer path) of air, losing more energy. Because the sun is overhead for only a short time, the air mass is normally greater than one—that is, the available energy is less than 1000 W/m².

3.1.1.d Air Mass

The standard spectrum of sunlight at the Earth's surface

✓ AM1.5G (where G stands for "global" and includes both direct and diffuse radiation)

✓ AM1.5D (which includes direct radiation only).

The number "1.5" indicates that the length of the path of light through the atmosphere is 1.5 times that of the shorter path when the sun is directly overhead.


✓ AMO is the standard spectrum outside the Earth's atmosphere where no light has yet passed through the atmosphere.

AM0 is typically used to predict the expected performance of PV cells in space.

 The intensity of AM1.5D radiation is approximated by reducing the AM0 spectrum by 28%, where 18% is absorbed and 10% is scattered.

•The global spectrum is 10% greater than the direct spectrum.

■These calculations give about 970 W/m² for AM1.5G. However, the standard AM1.5G spectrum is "normalized" to give 1000 W/m², because of inherent variations in incident solar radiation.



January 27, 2011

35

3.1.1e Irradiance on Plates

Direct light consists of radiation that comes straight from the sun
 Diffuse light is sunlight that is reflected off clouds, the ground, or other objects. It obviously takes a longer path than a direct light ray to reach a module.


Global sunlight is composed of direct-normal and diffuse components of sunlight.

Additionally, diffuse and direct-normal sunlight generally have different energy spectra or distributions of color.

3.1.1e Irradiance on Plates

What is the total irradiation on a solar plate?


http://www1.eere.energy.gov/solar/pv_cell_light.html



Flat-plate collectors, which typically contain a large number of solar cells mounted on a rigid, flat surface, can make use of both direct sunlight and the diffuse sunlight reflected from clouds, the ground, and nearby objects. ✓ The global irradiance on a horizontal surface on Earth consists of the direct irradiance E_{dir} and diffuse irradiance E_{dif} .

✓ On a tilted plane, there is another irradiance component: E_{ref} , which is the component that is reflected from the ground.

✓ Hence, the irradiance E_{tilt} on a tilted plane consists of three components: $E_{tilt} = E_{dir} + E_{dif} + E_{ref}$.



To find the site percent, add the numbers in the unshaded part of the sunpath arc. The site tracing shown here has 64% solar available for January, found by adding 2 + 3 + 4 + 5 + 6 + 7 + 7 + 8 + 8 + 6 = 64%. This shows that only 64% of the potential available radiation is reaching this particular location during January. 36% of the potential available radiation is blocked out in the middle of the winter.

3.1.1 Solar Energy

 A general analysis concludes that the energy available from sunlight on any fixed plate solar panel on earth depends on

☑ Time of year: Summer, Fall, Winter, Spring

- Altitude Angle (α)
- Zenith Angle (θ_z) .

☑ Location: Latitude/Longitude

☑ Time of Day

• Azimuth Angle (A_z)

Atmospheric Absorption

 Air mass. More specifically, the energy spectra falling onto the photovoltaic plate (this will be discussed in the next section)